

<p>Productnr.: 21.</p>  <p>100% Mercury free</p>  <p>Environmentally friendly</p> <p>Comparison: 36W fluorescent tube 3200lm with 360° + consumption ballast ca.43W 43 kWh/1000h</p>	<p>AGRO LED 120cm 20W 6000K frosted cover</p> <ul style="list-style-type: none"> - Low energy consumption of 17,7 Watt - 120° Radiation angle with 2.302 Lumen - Low heat development - Long lifetime up to 50,000 h - Diameter 26,3mm - Quicksilver- and lead-free 	<p>Productimage</p>  <p>cable side</p>  <p>blind side</p> <p>130,0 Lm/Watt</p>
	<p>Technical data:</p> <p>Voltage 230V / 50 Hz (from 100V up to 240V) Lightcolor (CCT) 6000 K +/- 200 K Total Lumen 2.302 Lm -> 130,0 Lm/Watt Radiation angle 120° / RA >80 Powerconsumption 17,7 Watt / cos phi > 0,964 Operation temperatue -20°C up to 40°C Temperature surface >1h max. ca. 45°C Diameter 26,3mm / Length with cable ±135cm Weight ±500 g (with cablelength 0,5m) Cable: 50cm YMvK DCA 2x2,5mm² (Ø10,5mm)</p> <p>CE certified und tested according EMV RoHS certified According EN60825-1 (VDE 0837 Part 1) Radiation safety with Laser and LED Single-sided power supply Durability LM80 (TM21) L90B50 > 50.000h Protection IP67 Not dimmable. 17,7 kWh /1000h</p>	<p>Single-sided power supply AC 230V 2x2,5mm²</p> 
<p>17,7 Watt 2.302 Lm</p> 	<p>Packaging information</p>  <p>Packingsunit: 173cm x 26cm x 22cm Packingsweight: 28 Kg # Lights in 1 pack: 48 pieces (with 0,5m cable)</p>	<p>Pictograms</p>   <p> double isolated / no grounding</p> <p> Fire safety certificate EN60598-2-24</p> 